

Datenblatt Art. 912.027

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

CONI Steckdosenleiste

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	0,2m H05VV-F 3G1,5mm ²	Supply cable	0,2m H05VV-F 3G1,5mm ²
Stecker	Wieland GST18i3	Plug	Wieland GST18i3
Stromausgang		Power output	
Steckdosen		Socket outlets	
2x CEE 7/3 (Type F)		2x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A 250V~, IP20		16A 250V~, IP20	
Funktionsmodule		Function modules	
Custom Module		Custom Modules	
2x Custom Module		2x Custom Modules	
Weitere Produkteigenschaften		Further product attributes	
Material		Material	
Gehäuse:		Housing:	
Aluminium, eloxiert		Aluminium, anodised	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x Steckdosenleiste CONI		1x Power strip Coni	
Im Karton		In carton	
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	IEC 60884, VDE 0620-1	Type approved	IEC 60884, VDE 0620-1