

Earthing contact plug 16 A / 250 V~

#	
<p>Central plug Large version Shatter-proof plastic Robust With strain relief and protective rubber sleeve With dual earthing contact system H05VV-F 3G 0.75/1.0/1.5 mm²</p>	
960.101	Black
960.201	White
960.301	Grey
<p>Central plug DIN 49441 Large version Shatter-proof plastic with strain relief H05VV-F 3G 1.0 mm²</p>	
910.971	Grey
<p>Central plug DIN 49441 Small version Shatter-proof plastic, with strain relief H05VV-F 3G 1.0 mm²</p>	
910.170	Black
910.270	White
910.470	Brown
<p>Right-angled plug Shatter-proof plastic Robust With strain relief and protective rubber sleeve With dual earthing contact system H05VV-F 3G 0.75/1.0/1.5 mm²</p>	
960.102	Black
960.202	White
960.302	Grey
<p>Right-angled plug Small version Shatter-proof plastic, with lateral earthing contact H05VV-F 3G 1.5 mm²</p>	
911.172	Black
911.272	White
<p>Flat plug/angled Shatter-proof design, with side entry H05VV-F 3G 1.50 mm²</p>	
911.170	Black
911.270	White
911.470	Brown
<p>Right-angled plug with switch Shatter-proof version made from plastic, with 2-pole rocker switch H05VV-F 3G 1.50 mm²</p>	
911.171	Black
911.271	White
<p>Right-angled plug with control switch Shatter-proof version made from plastic, with 2-pole illuminated rocker switch H05VV-F 3G 1.50 mm²</p>	
911.273	White
<p>Mounting plug Small version, shatter-proof plastic with separate strain relief, no parts that can be lost H05VV-F 3G 0.75/1.0/1.5 mm² With dual earthing contact system and nickel-plated contacts, e.g. Germany and France</p>	
910.100	Black
910.200	White



960.101



910.971



910.270



960.102



911.272



911.270



911.271



911.273



910.200